



Instructions for applying the antiSLIP system® to your floor

Step 1

1. Remove all the dirt and dust from the floor.
2. Mix half of the Step 1&3 packet with 2 parts water (1:2) → for professional use 4 parts water (1:4).
3. Apply this solution to the floor. Brush/mop the floor and make sure it is thoroughly cleaned and degreased.
4. Remove the solution and rinse the floor with clean water.
5. Allow the floor to dry.

Step 2

1. Pour the contents of the Step 2 packet into a large bucket.
2. WITHOUT DILUTING IT, apply this to the floor with a mop or a floor cloth.

IMPORTANT WARNING

- NEVER pour the contents of the bottle directly onto the floor.
 - DO NOT allow the product to drip onto the floor.
 - DO NOT stand in the liquid when applying the contents of the Step 2 packet.
 - If it drips or if there are footsteps, repeat the whole process from step 1 after the surface has been scrubbed with a hard brush.
3. Always use clean, preferably new, utensils.
 4. Apply the product for 3 minutes and do not allow it to dry, so that it can take effect.

Time table:

Natural stone (marble&Granite) and porcelain surfaces 5 minutes.

(always test a small part)

Glazed and unglazed floor tiles (ceramics) 3 minutes.

Concrete, cement and terrazzo surfaces 7-10 minutes.

NOTE: Do not remove the liquid from step 2. Apply step 3 directly on top of step 2.

Step 3

- Dilute the remaining half of the Step 1&3 with 2 parts water (1:2) → for professional use 4 parts water (1:4).



FLOOR SAFETY INNOVATIONS

Adres: Edisonstraat 15

Postcode: 2723 RS

Plaats: Zoetermeer

Tel: 079 - 34 34 670

Fax: 079 - 34 34 114

Email: fsi@antislip.org

- Apply this to the floor directly on top of the liquid from the Step 2 packet using a mop.
- Allow the solution to take effect for 1 minute.
- Remove the solution and rinse the floor with clean water.
- You now have an anti-slip floor. Try it straight away.

VERY IMPORTANT

For the correct treatment, it is recommended to not treat an area greater than 10 m² at a time, since the product dries very quickly when it comes into contact with a ceramic surface.

Tips

- Always test a small area of natural stone floors (Marble/ Granite/limestone).
- Always test a small area of the floor to be treated.

NEVER MAINTAIN ANTISLIP FLOORS WITH SOAP CLEANERS.