



FLOOR SAFETY INNOVATIONS

Adres: Edisonstraat 15
Postcode: 2723 RS
Plaats: Zoetermeer

Tel: 079 - 34 34 670
Fax: 079 - 34 34 114
Email: fsi@antislip.org

Instructions nonSLIP tape

Storage of nonSLIP tape

The tape must be stored in a dry place in its original packaging.

Treating the surface before application

The surface must be dry and free of grease before the tape can be applied. It is recommended to use a cleaning product/grease removing product that dissolves all the surface contamination. Advice: use IPA cleaners (Isopropyl alcohol). Do not use solvents/thinners or petrol-based cleaning products, because they leave behind a greasy film. After cleaning the surface, it must be dried with a lint-free cloth. If the surface is very absorbent, a special primer can be used.

Applying nonSLIP tape

Remove a piece (5 cm) of the protective foil on the rear of the tape and stick the tape to the clean surface. Next, carefully pull off the rest of the protective foil and stick the rest of the tape to the surface, making sure not to pull the tape too hard. NOTE: Do not apply the tape at a temperature below 10° C.

Finishing

After the nonSLIP tape has been applied, it is recommended to use a wallpaper roller to push the tape down. The sides of the tape can be sealed using a special edge sealer. This will increase the lifespan and improve the appearance in rooms where there is a lot of foot traffic. Floors on which the tape has been applied can be walked on immediately.