

## Product information sheet



### Producto

El sistema antiSLIP® es un producto invisible que se aplica en tres pasos.

Reduce el riesgo de resbalar en suelos húmedos. ¡No daña la superficie! También mantiene el brillo de la superficie, con excepción de las baldosas baratas que pueden perder un poco de brillo.

### Embalaje

Un paquete contiene 3 productos diferentes

1 botella de un líquido amarillo (paso 1/3)

1 botella de un líquido naranja (paso 2)

1 botella de un líquido azul (paso 4)

El paso 1/3 y el paso 2 forman juntos el sistema antiSLIP®,

El paso 4 es el producto de limpieza para el sistema antiSLIP®.

### Superficies que pueden tratarse:

El sistema antiSLIP® puede aplicarse en azulejos cerámicos (mate o con brillo), granito, baldosas de cuarzo, cemento, terrazo, bañeras de porcelana.

### Herramientas necesarias

2 cubos (para Paso 1/3 y Paso 2), guantes, gafas de seguridad, fregona/escoba, o una máquina de limpieza, trapo o bayeta, aspirador de agua. Limpiar siempre los utensilios después del tratamiento.

### Aplicable en los siguientes casos:

Piscinas, escuelas, hospitales, cocinas, residencias de ancianos, restaurantes, supermercados, edificios públicos, etc. y también en casa.



FLOOR SAFETY INNOVATIONS

**Adres:** Edisonstraat 15

**Postcode:** 2723 RS

**Plaats:** Zoetermeer

**Tel:** 079 - 34 34 670

**Fax:** 079 - 34 34 114

**Email:** fsi@antislip.org

!!!Es decir en todos aquellos lugares donde un suelo húmedo puede resultar peligroso!!!

### Technical data

- **Type of product;** step 1/3 Blend of glycol ethers and synthetic detergents. Indication on label of constituents according to EC regulation 684/2004. non-ionic surfactants: < 5% phosphates: < 5% perfume, limonene. Classification: not classified
- **Type of product;** step 2 Blend of inorganic acids and synthetic detergents. classification: corrosive. (always protect skin and eyes, and ventilate the area).
- **Type of product;** step 4 Blend of glycol ethers and synthetic detergents. Indication on label of constituents according to EC regulation 684/2004. non-ionic surfactants: < 5% phosphates: < 5% perfume, limonene. Classification: not classified
- **Mixing; step 1/3** ( 1:2 -- 1:4 depending the contamination of a surface)
- **Mixing; step 2** -- No this product must be used undiluted.
- **Mixing; step 4** ( 1:10 -- 1:40 depending the contamination of a surface)
- **Drying time;** no, after the 3 steps are done you can walk the treated surface.
- **UN Code:** 3264 (transport code)
- **Product codes;** Step 1/3 - 34022010 // Step 2 - 38249098
- **Product code;** Step 4 - 34022010
- **Application temperature;** between the 5°C and 30°C
- **Square meters;** with 1 Lit. antiSLIP system (1 Lit. step 1/3 and 1 Lit. step 2) you can treat 10 m<sup>2</sup>
- **Disposal Bottles:** At a chemical depot
- **Keep out of reach of children**

### Facts;

- It stops the bacterial growth after application of antiSLIP system®.
- Product is being sold world wide
- Tested by several independent testing labs
- Best and fastest applicable antislip product available

### CORROSIVE

Contains:





FLOOR SAFETY INNOVATIONS

**Adres:** Edisonstraat 15

**Postcode:** 2723 RS

**Plaats:** Zoetermeer

**Tel:** 079 - 34 34 670

**Fax:** 079 - 34 34 114

**Email:** fsi@antislip.org

Ammonium hydrogen difluoride

R34 Causes burns

R22 Harmful if swallowed

S1/2 Keep locked up and out of the reach of children

S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection